



## Certificate of Calibration and Compliance

Manufacturer : Viavi Solutions  
Model Number : Certifier40G  
Description : NGC-4500-FA  
Country of Manufacture : MALAYSIA  
Serial Number : jw20302223  
Calibration Report Number : 20302223-20171214  
Calibration Date : December 14, 2017  
Ambient Temperature : ( 23 ± 3 ) °C  
Relative Humidity : 30% to 70%

Viavi Solutions certifies that at the time of shipment the above listed instrument as identified by its serial number meets or exceeds all published specifications. It has been calibrated using standards with accuracies that are traceable to the National Institute of Standards and Technology (NIST) or other national laboratories. Accuracies have been derived from accepted values of physical constants, or have been derived by ratio type of self-calibration technique.

**Calibration Interval:**

The instrument has a calibration cycle of 12 months. Calibration does not deteriorate during storage prior to putting the instrument in active use. Calibration cycle of the instrument can be considered to start on the date the instrument was purchased by end user. First re-calibration will become due 12 months from that date.

Certificate Date  
December 14, 2017

Viavi Solutions  
Viavisolutions.com



Avda. Manoteras, 44 - 6ºB  
28050 Madrid  
Tel: 91 383 66 01  
C.I.F. A-70431483



## Certificate of Calibration and Compliance

Manufacturer : Viavi Solutions  
Model Number : Certifier40G  
Description : NGC-4500-FA  
Country of Manufacture : MALAYSIA  
Serial Number : jw20302224  
Calibration Report Number : 20302224-20171214  
Calibration Date : December 14, 2017  
Ambient Temperature : ( 23 ± 3 ) °C  
Relative Humidity : 30% to 70%

Viavi Solutions certifies that at the time of shipment the above listed instrument as identified by its serial number meets or exceeds all published specifications. It has been calibrated using standards with accuracies that are traceable to the National Institute of Standards and Technology (NIST) or other national laboratories. Accuracies have been derived from accepted values of physical constants, or have been derived by ratio type of self-calibration technique.

**Calibration Interval:**

The instrument has a calibration cycle of 12 months. Calibration does not deteriorate during storage prior to putting the instrument in active use. Calibration cycle of the instrument can be considered to start on the date the instrument was purchased by end user. First re-calibration will become due 12 months from that date.

Certificate Date  
December 14, 2017

Viavi Solutions  
Viavisolutions.com



Avda. Manoteras, 44 - 6ºB  
28050 Madrid  
Tel.: 91 383 96 01  
C.I.F.: A-76431489